



Boston Oak™

polytec

Installation & Product Guide

Architectural internal doors

Continuity in every detail. Designed for seamless spaces.

Designed to elevate both residential and commercial interiors, this refined 35mm door collection brings cohesion and continuity to your interiors. Featuring 15 Woodmatt colours with subtle woodgrain embossing, these doors bring warmth and texture to any space.

Doors are available in a variety of sizes, with heights from 2000mm to 2690mm and widths up to 1190mm, ensuring flexibility for different applications.

Discover **polytec**'s new Architectural internal door collection.

Product Availability | Architectural internal doors

Architectural internal doors | 35mm Decorative | MR LDF E-Zero | Max size 2690 x 1190mm

Name	Finish
Blossom White	Matt
Polar White	Matt
Oyster Grey	Matt
Blackened Oak	Woodmatt
Blonde Oak	Woodmatt
Boston Oak	Woodmatt
Botany Oak	Woodmatt
Bottega Oak	Woodmatt
Bronzed Oak	Woodmatt
District Oak	Woodmatt
Ecru Oak	Woodmatt
Hazel Oak	Woodmatt
Laurel Oak	Woodmatt
Manor Oak	Woodmatt
Prime Oak	Woodmatt
Rubra Oak	Woodmatt
Society Oak	Woodmatt
Tasmanian Oak	Woodmatt



Scan the QR code to view the
Architectural internal doors brochure.

Our selection of colours curated for contemporary interiors.

Colours in Woodmatt | Architectural internal doors



Colours in Solid Matt | Architectural internal doors



Installation & Fixing Recommendations | Architectural internal doors

When using 35mm Architectural internal doors, **polytec** strongly recommend the following fixing method, which is in line with the best practice already employed for hanging solid LDF doors.

1. 40mm long wood screws should be used.
2. 3mm diameter full depth pilot holes should be drilled.
3. 4 hinges should be used: bottom / middle / double hinged at the top.

The following criteria should be applied for hinged installation of 2700mm high solid LDF doors:

Hinges (not supplied)

Type: Flat Profile Non Mortice Hinge

Size: 100mm

Pin Type: Fixed or Loose

No. of Screws: Minimum of three (3) into door edge / Minimum of three (3) into door jamb

No. per Door: Four (4)

Hinge Placement:

- Double hinge at top
- 1st hinge at approximately 125mm from top of door
- 2nd hinge at approximately 350mm from top of door (ensure allowance for pin removal if loose pinned)
- 3rd hinge approximately at vertical midpoint of door
- 4th hinge at 150 - 250mm from bottom of door

For a modern, minimalistic look, **polytec** recommend using an aluminium door jam extrusion.



Scan the QR code for the latest
Installation & Product Guide.

Contact

For further information contact:

Porta Products Pty. Ltd. (ABN 31 003 246 357)

Address 2 Wella Way,
Somersby NSW 2250,
Australia

Telephone 1300 300 547

Fax 1300 320 547