

ULTRAGLAZE panels care

Your **ULTRAGLAZE** panels are manufactured from the highest quality materials and designed to provide years of trouble free service.

Do not remove the protective film until you have read the maintenance instructions listed below and only after all other trade work has been completed.

Whilst your panels are made from a Moisture Resistant Medium Density Fibreboard (MR MDF) and as with any wood based panel cannot be made totally waterproof, care should be taken to wipe up spills immediately, ensuring the doors are not exposed to high or continuous levels of moisture, steam and humidity.

General Cleaning

Wipe down using a damp soft cloth containing warm, soapy water.

For more stubborn stains, use a good quality streak free glass cleaner as per the manufacturers recommendation. Dry using a soft cloth so as not to leave any residue on the door or panel.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use.

To ensure that your **polytec** warranty will not be void:

DO NOT use any of the following on **polytec ULTRAGLAZE** doors & panels: Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids and Alkalis, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Acetone, Easy-Off BAM!, M.E.K. or any other cleaning agents containing organic solvents or the above mentioned products.

Avoid contact with sharp implements. Use range hoods whenever cooking, to avoid steam and cooking oil vapours from adversely effecting surfaces.

Please note: **polytec** provide a limited seven (7) year warranty on all door products which ensures against design, workmanship and manufacturing defects. If you detect any problems with your doors, **polytec** must be notified within seven (7) years from the date your doors were manufactured. Failure to follow the above care instructions may result in damage to your doors and void your entitlement to the warranty. **polytec's** warranty does not cover wear and tear. For More information refer to the **polytec** Products Limited Terms & Conditions document.

If used in a commercial application the warranty term is for 12 months (1 year) from the date of purchase.

Date of last update: March 2017